


# V420

# SKID LOADERS



**GEHL**®

Capacities		Metric	Imperial
Rated Operating Capacity		1905 kg	4199.80 lbs
Unladen weight		5291 kg	11664.65 lbs
Weight and dimensions			
Overall Operating Height - Fully Raised	h27	4744 mm	15 ft 6.77 in
Height to Hinge Pin – Fully Raised	h28	3653 mm	11 ft 11.81 in
Overall Height to Top of ROPS	h17	2083 mm	6 ft 10 in
Dump angle at full height	a5	31 °	31 °
Dump height	h29	2921 mm	9 ft 7 in
Overall length with bucket	l16	4039 mm	13 ft 3.01 in
Dump reach at full height		965 mm	3 ft 1.99 in
Rollback at ground		30 °	30 °
Wheelbase	y	1384 mm	4 ft 6.48 in
Overall width less bucket	b1	2057 mm	6 ft 8.98 in
Bucket Width	e1	2134 mm	7 ft 0.01 in
Ground clearance	m4	197 mm	7.75 in
Overall length - Less Bucket	l2	3124 mm	10 ft 2.99 in
Clearance Radius - Front with Bucket		2484 mm	8 ft 1.79 in
Clearance Circle - Front without Bucket	b19	1410 mm	4 ft 7.51 in
Clearance Circle - Rear	wa1	1880 mm	6 ft 2.01 in
Performances			
Travel Speed with Two-Speed Option - Maximum		18.70 km/h	11.61 mph
Wheels			
Standard tyres		14.00x17.5 HD	14.00x17.5 HD
Engine			
Engine brand		Deutz	Deutz
Engine model		TCD 3.6	TCD 3.6
Engine norm		Stage IV / Tier 4 Final	Stage IV / Tier 4 Final
Gross Power (kW)		90 kW	90 kW
Max. torque / Engine rotation		480 Nm / 2200 rpm	480 Nm / 2200 rpm
Battery		12 V	12 V
Starter (kW)		4 kW	4 kW
Hydraulics			
Standard flow - Auxiliary hydraulics		114 l/min	114 l/min
High-Flow Auxiliary Hydraulics – Option		155 l/min	155 l/min
Tank capacities			
Fuel tank		144 l	38.04 US gal
Reservoir Capacity Hydraulics		59.80 l	15.79 US gal
Displacement		3.60 l	0.95 US gal
Noise and vibration			
Environmental noise (LwA)		82.90 dB(A)	82.90 dB(A)
Whole-Body Vibration (ISO 2631-1)		1.09 m/s <sup>2</sup>	1.09 m/s <sup>2</sup>
Vibration to whole hand/arm		< 1.15 m/s <sup>2</sup>	< 1.15 m/s <sup>2</sup>



# GEHL®

Siège Social  
P.O. Box 179 - One Gehl Way - West Bend, WI, USA 53095  
Tel: (262) 334-9461 - Fax: (262) 338-7517  
[www.gehl.com](http://www.gehl.com)



This brochure describes versions and configuration options for Gehl products which may be fitted with different equipment. The equipment described in this brochure may be standard, optional or not available depending on version. Gehl reserves the right to change the specifications shown and described at any time and without prior warning. The manufacturer is not liable for the specifications given. For more information, contact your Gehl dealer. Non-contractual document. Product descriptions may differ from actual products. List of specifications is not comprehensive. The logos and visual identity of the company are the property of Gehl and may not be used without authorization. All rights reserved. The photos and diagrams contained in this brochure are provided for information only.

MANITOU EQUIPMENT AMERICAS, LLC - Limited company with board of directors - Share capital: 39,668,399 euros - 857 802 508 RCS West Bend